DECLARATION OF PERFORMANCE

NO. KWBFH-K518NF-001



01. Unique identification code of the product-type HD-Facing bricks category I,

240 x 115 x 71 mm

02. Item number

K518NF

03. Intended use

For structural or non-structural elements in unprotected or protected masonry

04. Manufacturer
Klinkerwerk B. Feldhaus GmbH & Co.
Nordring 1, 49196 Bad Laer, Germany

05. Not applicable

06. System 2+

07. The notified body for the factory production control CERT Baustoffe GmbH, Lübsche Straße 109, 23966 Wismar, Germany No. 2510 has performed the initial inspection of the factory and the factory production control as well as the continuous monitoring, evaluation and assessment of the factory production control and issued the certificate of conformity of the factory production control No. 2510-CPR-330.

08. Not applicable

| 09. Declar | ed perfor | mance | | |
|---------------------------------|---|--------|--------------------------------------|------------------------------------|
| Essential characteristics | | | Performance | Harmonised technical specification |
| Work size | Length/Width/Height [mm] | | | EN 771-1:2011 |
| Limit deviations | Mean value | Class | T _m | |
| | | Length | -10 mm, + 5 mm | |
| | | Width | ± 5 mm | |
| | | Height | ± 3 mm | |
| | Dimensional range | Class | R _m | |
| | | Length | 10 mm | |
| | | Width | 6 mm | |
| | | Height | 4 mm | |
| Shape according to para. 5.3.2 | | | c) | |
| Compressive strength | Category | | I | |
| | Mean value [N/mm²] | | ≥ 44 | |
| | Stress direction | | perpendicular to the bed joint | |
| Common hygroexpansivity | | | NPD | |
| Compound strength [N/mm²] | | | Tabulated value according to annex C | EN 998:2010 |
| Content of active soluble salts | Class | | S2 | EN 771-1:2011 |
| Reaction to fire | Euroclass | | A1 | |
| Water absorption [Mass-%] | | | ≤ 6 | |
| Water vapour permeability µ | | | 50/100 | EN 1745:2012 |
| Gross dry density | Mean value [kg/m³] | | 1550 | EN 771-1:2011 |
| | Deviation class | | D2 | |
| | Form, shape, measure- ments and tolerances | | see above | |
| Net dry density | Mean value [kg/m³] | | 2350 | |
| | Deviation class | | D2 | |
| Thermal conductivity [W/(m·K)] | | | NPD | |
| Durability Class | | | F2 | |
| Hazardous substances | | | annex ZA 3 | |

10. The performance of the product identified in points1 and 2 is in conformity with the declaredperformance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bad Laer: 26.10.2016

Bernhard Feldhaus, Managing Director